



Product data sheet

Product category	Portable Airco
Brand	Qlima
Model	P 228
Colour	White
EAN code	8713508783888

Technical specifications

EER ¹	W/W	2,6
Energy class		A
Cooling capacity - pdesignc	kW	2,8
Energy consumption - hourly indicative (Qsd/c)	kWh	1,076
Power supply	V/Hz/Ph	220 - 240~ / 50 / 1
Current (max)	A	4,8
Airflow (high) ²	m³/h	300
For rooms up to	m³	65 - 90
Dehumidification capacity ³	l/24 h	40,8
Operating range ²	°C	16 ~ 35
Thermostatic range	°C	16 ~ 31
Sound pressure noise level - high mode	dB	55
Sound power noise level at 1 m	dB(A)	65
Fan speeds	positions	3
Control		electronic / remote control
Included filters	type	nylon
Refrigerant type / charge	R/g	R290 / 230
Refrigerant GWP		3
Dimensions (w x d x h)	mm	440 x 335 x 715
Compressor type		rotary
CO ₂ equivalent	tonnes	0,00069
Protection class	IPxx	IPX0
Net. weight	kg	29
Guarantee	years	2

1 Measured conform EN 14511-2011

2 To be used as indication

3 Moisture removal at 32°C. 80% RH

Package content

Portable airconditioner, Remote control, AAA battery 2x, Filter, Drainage tube, Hose inlet, Hose outlet, User manual

Accessories (not included)

Description	EAN code





Remote control



3 Fan speeds



Cooldown function



R290 environmental friendly refrigerant



Dehumidifier function



Auto-stop function



Sleep mode

Features

Electronic controls: The unit is equipped with electronic controls.

Fan speed setting: Select the fan speed: low, medium or high. The display will show the chosen speed.

Timer: Operating time to be set to 24 hours. The unit switches off or on automatically when the set time has run down.

Air conditioning: The unit produces, with relatively high energy (A-rating), a pleasant and refreshing high capacity cool airflow. Unhealthy particles are captured by the air filters. Performance is optimal when the entering of warm outside air.

Airflow: Move the air vent direction by adjusting the grill at the front side of the air conditioner and by moving the vertical and horizontal louvers.

Cooldown effect: The unit removes humidity by condensation. The condensate cools the condenser and is removed by the hot air discharge. This will increase the energy efficiency, the so called "cool down" effect.

Dehumidification: The unit can also be used as a dehumidifier only. In that case the exhaust hose is not connected and warm air returns in the room.

Continuous drainage: In use as dehumidifier it is necessary to connect a continuous drainage tube (not included) to the unit.

Full colour box: The unit is delivered complete with auxiliary parts in a stylish full colour box showing application and operation information in multiple languages.
